

Commands: pwd, cd, mkdir, rmdir

```
pubsrv1:/tmp>pwd
/tmp
pubsrv1:/tmp>ls -as
total 82
 16 .                      16 junk                     16 sh5720
  2 ..                      0 mysql.sock
 16 hsperfdata_reserv      0 output26675
 16 hsperfdata_root        0 output26935
pubsrv1:/tmp>ls -lF
total 64
drwxr-xr-x  2 reserv     other          177 Jan 24 16:22 hsperfdata_reserv/
drwxr-xr-x  2 root       root           117 Feb 15 02:24 hsperfdata_root/
drwx----- 2 antoulas   other          238 Feb 16 00:07 junk/
srwxrwxrwx  1 mysql      mysql          0 Jan 24 16:22 mysql.sock=
-rw-r--r--  1 vfisikop   doctoral        0 Jan 27 14:27 output26675
-rw-r--r--  1 vfisikop   doctoral        0 Jan 27 14:29 output26935
-rw------- 1 root       root          849 Jan 24 16:22 sh5720

pubsrv1:/tmp>mkdir subdir
pubsrv1:/tmp>ls -lF
total 80
drwxr-xr-x  2 reserv     other          177 Jan 24 16:22 hsperfdata_reserv/
drwxr-xr-x  2 root       root           117 Feb 15 02:24 hsperfdata_root/
drwx----- 2 antoulas   other          238 Feb 16 00:07 junk/
srwxrwxrwx  1 mysql      mysql          0 Jan 24 16:22 mysql.sock=
-rw-r--r--  1 vfisikop   doctoral        0 Jan 27 14:27 output26675
-rw-r--r--  1 vfisikop   doctoral        0 Jan 27 14:29 output26935
-rw------- 1 root       root          849 Jan 24 16:22 sh5720
drwx----- 2 antoulas   other         117 Feb 16 01:04 subdir/
```

Commands: pwd, cd, mkdir, rmdir

```
pubsrv1:/tmp>pwd
pubsrv1:/tmp>cd subdir/
pubsrv1:/tmp/subdir>ls -las
total 32
 16 drwx----- 2 antoulas other          117 Feb 16 01:04 .
 16 drwxrwxrwt  6 root      sys          653 Feb 16 01:05 ..
.
pubsrv1:/tmp/subdir>pwd
/tmp/subdir
pubsrv1:/tmp/subdir>cd ..
pubsrv1:/tmp>rmdir subdir/
pubsrv1:/tmp>ls subdir
subdir: No such file or directory
pubsrv1:
```

Commands: cp (-i, -r), mv (-i), rm (-i, -r, -f)

- ▶ “-i”: interactive mode (asks before an action can be taken).
- ▶ “-r”: option about directories in cp and rm commands
- ▶ “-f”: force option (in removing files/directories).
- ▶ “rm -f” is less powerful than “rm -i”

Command: rm

```
pubsrv1:/tmp>cd junk/
pubsrv1:/tmp/junk>ls
aaa    bbbb
pubsrv1:/tmp/junk>rm -fi bbbb
rm: remove bbbb (yes/no)? y
pubsrv1:/tmp/junk>ls
aaa
pubsrv1:/tmp/junk>rm -f aaa
rm: remove aaa (yes/no)? n
pubsrv1:/tmp/junk>alias rm
rm -i
pubsrv1:/tmp/junk>unalias rm
pubsrv1:/tmp/junk>rm -fi aaa
rm: remove aaa (yes/no)? n
pubsrv1:/tmp/junk>rm -f aaa
pubsrv1:/tmp/junk>ls
pubsrv1:/tmp/junk>
```

Commands: more, cat

```
antoulas@sazerac:/tmp$ more .bashrc
# .bashrc file
# User specific aliases and functions

# Source definitions
if [ -f /etc/bashrc ]; then
    . /etc/bashrc
fi

alias ll='ls -l'
alias la='ls -A'
alias l='ls -CF'

PS1='\$ '
antoulas@sazerac:/tmp$ cat -n .bashrc
 1 # .bashrc file
 2 # User specific aliases and functions
 3
 4 # Source definitions
 5 if [ -f /etc/bashrc ]; then
 6     . /etc/bashrc
 7 fi
 8
 9 alias ll='ls -l'
10 alias la='ls -A'
11 alias l='ls -CF'
12
13 PS1='\$ '
antoulas@sazerac:/tmp$
```

Command: lpr, lpstat -t

```
antoulas@sazerac:/tmp$ lpstat -t
scheduler is running
system default destination: hp-LaserJet-1320-series
device for hp-LaserJet-1320-series: usb://HP/LaserJet%201320%20series
hp-LaserJet-1320-series accepting requests since Tue 12 Jan 2010 11:37:50 AM EET
printer hp-LaserJet-1320-series is idle. enabled since Tue 12 Jan 2010 11:37:50
AM EET
antoulas@sazerac:/tmp$
antoulas@sazerac:/tmp$ lpr -P hp-LaserJet-1320-series .bashrc
antoulas@sazerac:/tmp$
antoulas@sazerac:/tmp$ lpstat -t
scheduler is running
system default destination: hp-LaserJet-1320-series
device for hp-LaserJet-1320-series: usb://HP/LaserJet%201320%20series
hp-LaserJet-1320-series accepting requests since Tue 16 Feb 2010 01:50:49 AM EET
printer hp-LaserJet-1320-series is idle. enabled since Tue 16 Feb 2010 01:50:49
AM EET
    Printer is now online.
antoulas@sazerac:/tmp$
```

Text Editors for Creating ASCII Files

- ▶ `vi/vim <filename>`: edit the content of the file with name `<filename>`
 - ◊ Two modes of operations: *input* and *edit*
 - ◊ Move from input to edit with ESC button.
 - ◊ Move from edit to input mode by pressing “i”
- ▶ www.yolinux.com/TUTORIALS/LinuxTutorialAdvanced_vi.html
- ▶ `emacs`
- ▶ `pico`
- ▶ `ed` (ancient)
- ▶ `gedit, xemacs, etc.`

Commands for processing ASCII files

chmod	change access rights for files and catalogs
more	page-by-page display of file content
less	forward/backward display of a file content
grep	search for a specific symbol patterns in a file
wc	lexical statistics for files
sort	sort the lines of a text file
ln	create links
cut	display portion of lines from a file
cmp	compare two files
diff	display differences between two files
head	display top-k lines of a file
tail	display bottom-k lines of a file
touch	change the timestamp or create a file

Command: chmod

```
antoulas@sazerac:/tmp/junk$ ls -las
total 48
4 drwxr-xr-x 2 antoulas    antoulas  4096 2010-02-16 02:44 .
40 drwxrwxrwt 18 root       root      36864 2010-02-16 02:43 ..
4 -rw-r--r-- 1 antoulas    antoulas   184 2010-02-16 02:44 .bashrc
antoulas@sazerac:/tmp/junk$ cp .bashrc tmp1
antoulas@sazerac:/tmp/junk$ ls -l
total 4
-rw-r--r-- 1 antoulas _developer 184 2010-02-16 02:44 tmp1
antoulas@sazerac:/tmp/junk$ mkdir bin
antoulas@sazerac:/tmp/junk$ ls -l
total 8
drwxr-xr-x 2 antoulas _developer 4096 2010-02-16 02:44 bin
-rw-r--r-- 1 antoulas _developer 184 2010-02-16 02:44 tmp1
antoulas@sazerac:/tmp/junk$ chmod g-r tmp1
antoulas@sazerac:/tmp/junk$ chmod g+wx tmp1
antoulas@sazerac:/tmp/junk$ ls -l
total 8
drwxr-xr-x 2 antoulas _developer 4096 2010-02-16 02:44 bin
-rw--wxr-- 1 antoulas _developer 184 2010-02-16 02:44 tmp1
antoulas@sazerac:/tmp/junk$ chmod u-wx,g=rx,o+x tmp1
antoulas@sazerac:/tmp/junk$ ls -l
total 8
drwxr-xr-x 2 antoulas _developer 4096 2010-02-16 02:44 bin
-r--r-xr-x 1 antoulas _developer 184 2010-02-16 02:44 tmp1
antoulas@sazerac:/tmp/junk$ rm tmp1
rm: remove write-protected regular file 'tmp1'? y
```

```
antoulas@sazerac:/tmp/junk$ ls -las
total 52
4 drwxr-xr-x 3 antoulas antoulas 4096 2010-02-16 02:46 .
40 drwxrwxrwt 18 root      root    36864 2010-02-16 02:43 ..
4 -rw-r--r-- 1 antoulas antoulas   184 2010-02-16 02:44 .bashrc
4 drwxr-xr-x 2 antoulas antoulas 4096 2010-02-16 02:44 bin
antoulas@sazerac:/tmp/junk$ cp -r /tmp/mydir .
antoulas@sazerac:/tmp/junk$ ls -Rl
.:
total 8
drwxr-xr-x 2 antoulas _developer 4096 2010-02-16 02:44 bin
drwxr-xr-x 2 antoulas _developer 4096 2010-02-16 02:48 mydir
./bin:
total 0
./mydir:
total 8
-rwxr-xr-x 1 antoulas _developer 14 2010-02-16 02:48 A1
-rwxr-xr-x 1 antoulas _developer 20 2010-02-16 02:48 A2
antoulas@sazerac:/tmp/junk$ chmod -R 700 mydir/
antoulas@sazerac:/tmp/junk$ ls -lR mydir/
mydir/:
total 8
-rwx----- 1 antoulas _developer 14 2010-02-16 02:48 A1
-rwx----- 1 antoulas _developer 20 2010-02-16 02:48 A2
antoulas@sazerac:/tmp/junk$ ls -lasR mydir/
mydir/:
total 16
4 drwx----- 2 antoulas _developer 4096 2010-02-16 02:48 .
4 drwxr-xr-x 4 antoulas _developer 4096 2010-02-16 02:48 ..
4 -rwx----- 1 antoulas _developer   14 2010-02-16 02:48 A1
4 -rwx----- 1 antoulas _developer   20 2010-02-16 02:48 A2
antoulas@sazerac:/tmp/junk$
```

Command: less

```
antoulas@sazerac:~/set001$ less set001.tex
\documentclass[]{beamer}
% Theme for beamer presentation.
\usepackage{beamertemelined}
% \usepackage{beamertemeshsplit}
% Other themes include: beamertemebars, beamertemelined,
%                         beamertememetree, beamertememetreebars

\usepackage{algorithmic}
\usepackage{listings}
\usepackage{pifont}
\usepackage{color}
\usepackage{hyperref}
\newcommand{\crossout}{\ding{55}>

\newenvironment{pk1}{%
\begin{itemize}%
\vspace{-\topsep}%
\setlength\itemsep{-\parskip}%
set001.tex
```

- ◇ [return] - skip a line; [space] - get next page;
b: display previous page; /<s>: search for pattern s;
!<c>[return]: execute command c; h: help;
q: exit from less

Command: grep

```
antoulas@sazerac:/var/log$  
antoulas@sazerac:/var/log$ grep x86 dmesg  
[    0.000000] Transmeta GenuineTMx86  
[    0.000000] x86 PAT enabled: cpu 0, old 0x7040600070406, new 0x7010600070106  
[    0.000000] Using x86 segment limits to approximate NX protection  
[    0.004000] x86 PAT enabled: cpu 1, old 0x7040600070406, new 0x7010600070106  
[ 10.148624] NVRM: loading NVIDIA UNIX x86 Kernel Module 185.18.36 Fri Aug  
14 17:18:04 PDT 2009  
antoulas@sazerac:/var/log$  
antoulas@sazerac:/var/log$ grep -n x86 dmesg  
10:[    0.000000] Transmeta GenuineTMx86  
41:[    0.000000] x86 PAT enabled: cpu 0, old 0x7040600070406, new 0  
x7010600070106  
58:[    0.000000] Using x86 segment limits to approximate NX protection  
212:[    0.004000] x86 PAT enabled: cpu 1, old 0x7040600070406, new 0  
x7010600070106  
737:[ 10.148624] NVRM: loading NVIDIA UNIX x86 Kernel Module 185.18.36 Fri  
Aug 14 17:18:04 PDT 2009  
antoulas@sazerac:/var/log$  
antoulas@sazerac:/var/log$ grep -i CoOLing dmesg  
[    0.414599] processor LNXCPU:00: registered as cooling_device0  
[    0.414803] processor LNXCPU:01: registered as cooling_device1  
antoulas@sazerac:/var/log$
```


Command wc

```
antoulas@sazerac:~/set001/Samples$ ls
aaa bbbb lista Set-01.ppt zzz
antoulas@sazerac:~/set001/Samples$ wc lista
10 30 183 lista
antoulas@sazerac:~/set001/Samples$ wc -w lista
30 lista
antoulas@sazerac:~/set001/Samples$ wc -l lista
10 lista
antoulas@sazerac:~/set001/Samples$ wc -c lista
183 lista
antoulas@sazerac:~/set001/Samples$ wc -lc lista
10 183 lista
antoulas@sazerac:~/set001/Samples$ wc -lw lista
10 30 lista
antoulas@sazerac:~/set001/Samples$
```

Command sort

```
antoulas@sazerac:~/set001/Samples$ cat lista
john      32    london
eduardo   19    brazilia
jean      21    athens
marco     7     buenosaires
filip      23    telaviv
dennis    15    brisbane
louis     31    heraclion
dimi      34    heraclion
ji         27    washington
hyseyin   33    izmir
antoulas@sazerac:~/set001/Samples$ sort lista
dennis    15    brisbane
dimi      34    heraclion
eduardo   19    brazilia
filip      23    telaviv
hyseyin   33    izmir
jean      21    athens
ji         27    washington
john      32    london
louis     31    heraclion
marco     7     buenosaires
antoulas@sazerac:~/set001/Samples$
```


Using the Delimiters in sort



- ▶ When a field for sorting is needed: $+number_1 - number_2$
- ▶ $number_1$: specifies the number of fields to be skipped to get to the beginning of the sort filed.
- ▶ $number_2$: specifies the number of fileds to be skipped, relative to the beginning of the line, to get to the end of the sort key.

Delimiter Examples

Field Specification



```
antoulas@sazerac:~/set001/Samples$ sort +0 -1 lista
dennis 15 brisbane
dimi 34 heraclion
eduardo 19 brasilia
filip 23 telaviv
hyseyin 33 izmir
jean 21 athens
ji 27 washington
john 32 london
louis 31 heraclion
marco 7 buenosaires
antoulas@sazerac:~/set001/Samples$ sort -r -u +2 -3 lista
ji 27 washington
filip 23 telaviv
john 32 london
hyseyin 33 izmir
louis 31 heraclion
marco 7 buenosaires
dennis 15 brisbane
eduardo 19 brasilia
jean 21 athens
antoulas@sazerac:~/set001/Samples$ sort -r +2 -3 lista
ji 27 washington
filip 23 telaviv
john 32 london
hyseyin 33 izmir
louis 31 heraclion
dimi 34 heraclion
marco 7 buenosaires
dennis 15 brisbane
eduardo 19 brasilia
jean 21 athens
```

```
antoulas@sazerac:~/set001/Samples$ sort -r -n +1 -2 lista
dimi      34  heraclion
hyseyin  33  izmir
john     32  london
louis    31  heraclion
ji       27  washington
filip    23  telaviv
jean    21  athens
eduardo 19  brasilia
dennis   15  brisbane
marco    7   buenosaires
antoulas@sazerac:~/set001/Samples$ sort -u +1 -4 lista
dennis   15  brisbane
eduardo 19  brasilia
jean    21  athens
filip    23  telaviv
ji       27  washington
louis    31  heraclion
john     32  london
hyseyin  33  izmir
dimi     34  heraclion
marco    7   buenosaires
antoulas@sazerac:~/set001/Samples$
```

Command touch (change timestamp or create an empty file)

```
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ ls
aaa bbbb lista Set-01.ppt zzz
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ touch
    antoulas
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ ls -l
total 10464
-rwxr-xr-x 1 antoulas _developer      15 2010-02-18 08:42
    aaa
-rwxr-xr-x 1 antoulas _developer      1200 2010-02-18 08:42
    bbbb
-rwxr-xr-x 1 antoulas _developer      0 2010-02-18 12:16
    antoulas
-rwxr-xr-x 1 antoulas _developer      183 2010-02-18 08:42
    lista
-rwxr-xr-x 1 antoulas _developer 10583040 2010-02-18 08:42
    Set-01.ppt
-rwxr-xr-x 1 antoulas _developer      72 2010-02-18 08:42
    zzz
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ touch aaa
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ ls -l
total 10464
-rwxr-xr-x 1 antoulas _developer      15 2010-02-18 12:16
    aaa
-rwxr-xr-x 1 antoulas _developer      1200 2010-02-18 08:42
```

Hard Links with ln

```
antoulas@sazerac:~/set001/Samples$ ln bbbb myhardlink
antoulas@sazerac:~/set001/Samples$ ls -l
total 10356
-rwxr-xr-x 1 antoulas _developer      15 2010-02-18 12:25 aaa
-rwxr-xr-x 2 antoulas _developer    1200 2010-02-18 12:27 bbbb
-rwxr-xr-x 1 antoulas _developer        0 2010-02-18 12:25 antoulas
-rwxr-xr-x 1 antoulas _developer     183 2010-02-18 12:25 lista
-rwxr-xr-x 2 antoulas _developer    1200 2010-02-18 12:27 myhardlink
-rwxr-xr-x 1 antoulas _developer 10583040 2010-02-18 12:25 Set-01.ppt
-rwxr-xr-x 1 antoulas _developer      72 2010-02-18 12:25 zzz
antoulas@sazerac:~/set001/Samples$ ls -i bbbb myhardlink
691247 bbbb 691247 myhardlink
antoulas@sazerac:~/set001/Samples$ cp bbbb eeee
antoulas@sazerac:~/set001/Samples$ ls -li bbbb myhardlink eeee
691247 -rwxr-xr-x 2 antoulas _developer 1200 2010-02-18 12:27 bbbb
691204 -rwxr-xr-x 1 antoulas _developer 1200 2010-02-18 12:34 eeee
691247 -rwxr-xr-x 2 antoulas _developer 1200 2010-02-18 12:27 myhardlink
antoulas@sazerac:~/set001/Samples$ diff bbbb myhardlink
antoulas@sazerac:~/set001/Samples$ rm bbbb
antoulas@sazerac:~/set001/Samples$ ls -l myhardlink
-rwxr-xr-x 1 antoulas _developer 1200 2010-02-18 12:27 myhardlink
antoulas@sazerac:~/set001/Samples$ cp myhardlink bbbb
antoulas@sazerac:~/set001/Samples$ ls -l
total 10360
-rwxr-xr-x 1 antoulas _developer      15 2010-02-18 12:25 aaa
-rwxr-xr-x 1 antoulas _developer    1200 2010-02-18 12:35 bbbb
-rwxr-xr-x 1 antoulas _developer        0 2010-02-18 12:25 antoulas
-rwxr-xr-x 1 antoulas _developer    1200 2010-02-18 12:34 eeee
-rwxr-xr-x 1 antoulas _developer     183 2010-02-18 12:25 lista
-rwxr-xr-x 1 antoulas _developer    1200 2010-02-18 12:27 myhardlink
-rwxr-xr-x 1 antoulas _developer 10583040 2010-02-18 12:25 Set-01.ppt
-rwxr-xr-x 1 antoulas _developer      72 2010-02-18 12:25 zzz
antoulas@sazerac:~/set001/Samples$
```

Soft links with ln -s

```
antoulas@sazerac:~/set001/Samples$ ls
aaa  bbbb  antoulas  eeee  lista  myhardlink  Set-01.ppt
      zzz
antoulas@sazerac:~/set001/Samples$ ln -s bbbb mysoftlink
antoulas@sazerac:~/set001/Samples$ ls -l mysoftlink
lrwxrwxrwx 1 antoulas _developer 4 2010-02-18 12:43
      mysoftlink -> bbbb
antoulas@sazerac:~/set001/Samples$ file *
aaa:          ASCII text
bbbb:          ASCII text
antoulas:     empty
eeee:          ASCII text
lista:         ASCII text
myhardlink:    ASCII text
mysoftlink:    symbolic link to 'bbbb'
Set-01.ppt:   CDF V2 Document, corrupt: Can't expand
              summary_info
zzz:          ASCII text
antoulas@sazerac:~/set001/Samples$ rm bbbb
antoulas@sazerac:~/set001/Samples$ ls
aaa  antoulas  eeee  lista  myhardlink  mysoftlink  Set-01.
      ppt  zzz
antoulas@sazerac:~/set001/Samples$ more mysoftlink
mysoftlink: No such file or directory
```

Comparison between soft/hard links

Hard Links	Soft Links
“Pointer” to the initial file	Copy of the path to the initial file
Does not apply to directories	Applies to directories
Name change of the initial file does not create any problems	Name change in the initial file creates problems
Content changes in initial file are reflected in the link as well	Content changes in initial file are reflected in the link as well
File gets purged when <i>all</i> links are deleted	Deletion of initial file affects the link (point to non-existing file)

Command cut: -f: designates column selection, -d designates delimiter

```
antoulas@sazerac:~/set001/Samples$ cat lista1
123:jim:morrison:2103456789:reading
345:peter:gabriel:4567891234:london
673:pete:garret:9602345612:sydney
133:time:machine:3452678967:moscow
231:kitrina:podilata:2138905674:athens
antoulas@sazerac:~/set001/Samples$
antoulas@sazerac:~/set001/Samples$ cut -f3,2 -d':' lista1
jim:morrison
peter:gabriel
pete:garret
time:machine
kitrina:podilata
antoulas@sazerac:~/set001/Samples$
antoulas@sazerac:~/set001/Samples$ cut -f1-3 -d':' lista1
123:jim:morrison
345:peter:gabriel
673:pete:garret
133:time:machine
231:kitrina:podilata
antoulas@sazerac:~/set001/Samples$
```

Commands: cmp, diff, head, tail

```
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ ls lista*
lista  lista1  lista2  lista3
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ cmp lista lista3
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ diff lista lista2
4c4
< marco    buenosaires
---
> marco 97  buenosaires
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ head lista2
john      32  london
eduardo   19  brasilia
jean      21  athens
marco     97  buenosaires
filip      23  telaviv
dennis     15  brisbane
louis      31  heraclion
dimi       34  heraclion
ji         27  washington
hyseyin   33  izmir
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ head -3 lista2
john      32  london
eduardo   19  brasilia
jean      21  athens
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$ tail -3 lista2
dimi      34  heraclion
ji        27  washington
hyseyin  33  izmir
antoulas@sazerac:/media/2CD3-FD08/set001/Samples$
```

Commands echo, whoami, hostname, lpq/lpstat -t, lprm

```
antoulas@sazerac:~/set001/Samples$ echo this is a test for k24
this is a test for k24
antoulas@sazerac:~/set001/Samples$ echo -n this is a test for k24
this is a test for k24antoulas@sazerac:~/set001/Samples$ 
antoulas@sazerac:~/set001/Samples$ 
antoulas@sazerac:~/set001/Samples$ whoami
antoulas
antoulas@sazerac:~/set001/Samples$ hostname
sazerac
antoulas@sazerac:~/set001/Samples$ lpr Set-01.ps
antoulas@sazerac:~/set001/Samples$ lpq
hp-LaserJet-1320-series is ready and printing
Rank      Owner      Job      File(s)                      Total Size
1st       antoulas   143     Set-01                   12930048 bytes
antoulas@sazerac:~/set001/Samples$ lprm -Php-LaserJet-1320-series 143
antoulas@sazerac:~/set001/Samples$ lpq
hp-LaserJet-1320-series is ready and printing
Rank      Owner      Job      File(s)                      Total Size
antoulas@sazerac:~/set001/Samples$ lpstat -t
scheduler is running
system default destination: hp-LaserJet-1320-series
device for hp-LaserJet-1320-series: usb://HP/LaserJet%201320%20series
hp-LaserJet-1320-series accepting requests since Fri 19 Feb 2010 01:03:52 PM EET
printer hp-LaserJet-1320-series is idle. enabled since Fri 19 Feb 2010 01:03:52
    PM EET
    Printer is now online.
antoulas@sazerac:~/set001/Samples$
```

Shells (csh, tcsh, bash, kornsh, etc.)

- ▶ Once “connected” to a tty in LINUX you are provided with a default bash shell.
- ▶ logout severs the authenticated session the user maintains.
- ▶ exit or control-d disconnect terminates the shell session.
- ▶ You can go to csh or tcsh by simply typing tcsh or csh.
- ▶ Once a shell is initiated, some file (e.g. `~/.cshrc`) is executed.
- ▶ As soon as a user logs into a system, the commands in file `.login` are executed.
- ▶ Once a user logouts from the system the shell commands in file `.logout` are executed.

Shell (input/output)

Every shell has three predefined I/O means of communicating with the user:

- ▶ *stdin*: standard input (often the keyboard)
- ▶ *stdout*: standard output (often the screen)
- ▶ *stderr*: standard error (often the screen)
- ▶ file descriptors for the above files are 0, 1, 2 respectively.

For a number of system programs including cat, lpr, grep, wc, sort, head, tail etc., the file parameters are optional:

```
antoulas@sazerac:~/set001/Samples$ wc
this is a test - this is only
a test, this is a test
this is only a test
this is a
test
only
bye
{control-d}
    7      25     100
antoulas@sazerac:~/set001/Samples$
```

csh redirection

- Redirection of the *stdin*:

```
antoulas@sazerac:~/set001$  
antoulas@sazerac:~/set001$ csh  
%  
%  
% grep clio lista  
louis    31  heraclion  
dimi     34  heraclion  
% grep clio < lista  
louis    31  heraclion  
dimi     34  heraclion  
% grep bra < lista > out1  
% cat out1  
eduardo 19  brasilia
```